

Bamburgh House, Cuthbertbank Road Sheffield, South Yorkshire. S6 2HP Tel: 0114 2313133 Fax: 0114 2313144

orders@bifoldnetwork.com quotes@bifoldnetwork.com



Order Quotation Leadtime: Up to 24 hrs Order confirmation Leadtime: Up to 24 hrs Quote Ref Date Customer PLEASE GIVE EXTERNAL TIMBER UPSTAND MEASUREMENTS E.T.U The guidelines for designing Stratus Lantern roofs are as follows: -1. Fixed 20° pitch 2. No Jack rafters 150mm 150mm 3. 24mm glazing only 4. Minimum ridge length 140mm 5. Maximum rafter spacing 1500mm The required timber upstand size is 100mm x 150mm based on E.T.U size 6. External caps are aluminium, internal You must advise us if different. Please call to check ETU sizes before PVC-u. Stock colours are white, creating the opening, to make sure lantern will look aesthetically pleasing anthracite grey & black. We can powder coat to any RAL please ask for **ROOF SKETCH** further information 7. Sizes relate to external face of timber up-stand (E.T.U) E.T.U WIDTH 8. For optimum looks: -Width x 1.5/2/2.5 Example 1400 (w) x 2100 (l) **E.T.U** LENGTH **ROOF COLOUR ROOF GLAZING MAXIMUM SIZES** EXT INT Ambi-Blue (1.2 u value unit) White (RAL 9016) **HIP BARS ONLY** (supplied as standard) MAX 1500 x 3000m Anthracite grey (RAL 7016) ☐ Easyclean Clear/Low E (1.2 u value unit) Black (RAL 9005) 2 WAY STRATUS ☐ Ambi-Blue (1.0 u value unit) MAX 1500 x 6000m Other (Give RAL colour) ☐ Easyclean Clear/Low E (1.0 u value unit) 3 WAY STRATUS **EXT** Other please specify MAX 3000 x 6000m INT **MAXIMUM SIZES REFERT E.T.U** Notes/Special requests; Date Date required Collection Delivery **Delivery address** Print Signed